

ANTI-RAM DETERRENT bollards

>> New Finish: galvanised and painted only <<



TECHNICAL SPECIFICATIONS

- > Overall height with curved head :
 - 1238 mm (Ø 160 mm)
 - 1264 mm (Ø 219 mm)
 - 1270 mm (Ø 273 mm)
- > Recommended height above ground: 800 mm
- > Metal thickness: 4 mm
- > 2 versions available:
 - With Dome top cap in steel
 - With brushed stainless steel top cap (Ø 160 and Ø 219 mm only)



INSTALLATION RECOMMENDATIONS

- > Large steel & cast iron bollards are supplied empty with a flat iron welded inside for easy positioning using lifting equipment
- > Fill the bollard with reinforcement, then with concrete and add the curved head, sealed in the concrete by its hook

REFERENCES

	Galvanised	NEW Galvanised and painted	Zinc rich primer and painted
Ø 160 mm	206517	206790	206516
Ø 160 mm Brushed stainless steel lid	-	206791	206577
Ø 219 mm	206446	206792	206444
Ø 219 mm Brushed stainless steel lid	-	206793	206539
Ø 273 mm	206447	206794	206445

PAINT FINISH

- > Finish galvanised, painted on galvanised or zinc rich primer and painted on zinc according to our colours

RAL 3020	RAL 3004	RAL 5010	RAL 6005	RAL 8017	Galvanised
RAL 7044	RAL 9010	RAL 9005	PROCITY® Grey	Corten effect	



Ref. 206516
Ø 160 mm




Ref. 206539
Ø 219 mm



Ref. 206445
Ø 273 mm



Ref. 206517
Ø 160 mm



Ref. 206539
Ø 219 mm
Brushed stainless steel lid

DIAGRAM

