BLACK BULL FLEX+ guardrail posts, Polymer, black/yellow, S-Line with corner underride guard

Flexible S-Line impact protection guardrail with underride guard

The BLACK BULL FLEX+ S-Line impact protection guardrail with underride guard is a reliable choice for personal protection wherever pedestrians and internal traffic meet and there are additional hazards at ground level. While conventional guardrails primarily protect at vehicle height, the integrated underride guard additionally secures the ground level - and thus prevents forks from entering pedestrian areas. It ensures safe separation of walkways, workplaces and traffic areas and is used in warehouses, logistics and production. The combination of S-Line guardrail and underride guard creates a continuous line of protection for personal safety - from the ground to standing height.

Instead of rigid barriers, the system relies on controlled absorption: It absorbs impact energy, distributes forces across the entire protection line and then returns to its original shape automatically. This means that the protective function is retained even after an impact.

What happens in detail in the event of an impact

Crossbars & posts

The polymer crossbars of the S-Line form a clearly visible protective line and prevent vehicles from entering pedestrian areas. The integrated underride guard additionally secures the ground level and protects against forks, tires and collision damage. The posts absorb the transmitted forces and ensure stability along the entire safety line. Result: maximum personal protection, reduced accident risks, safe working areas.

Connections & junctions

The FlexLink connection technology distributes the forces evenly across the entire system. Point loads are avoided, individual components as well as the floor and anchor points are relieved. Result: Permanently stable guard lines without loose posts or consequential damage.

Base

The FLEX+ Base connects the posts to the Base ground anchor and forms an impact-resistant outer shell. It protects the internal screw connection and prevents damage to the tires of industrial trucks. The result: high suitability for everyday use and reduced maintenance.

Base floor anchor

The FLEX+ Base floor anchor combines robust anchoring in concrete with force-absorbing rubber dampers. This design reduces the load on the screw connection, protects the substrate and ensures a permanently stable attachment - even with repeated approaches.

Multiple impacts? No problem.

FLEX+ is made for everyday use. The system remains functional, especially after repeated bumps. No permanent deformation. Durable plastic thanks to high elasticity. This significantly reduces downtimes and follow-up costs.

Typical application scenarios for the FLEX+ S-Line impact protection railing with underrun protection

This solution is particularly suitable for areas with high pedestrian traffic and additional protection requirements at ground level: separation of walkways and

Important note: The information is based on manufacturer data as well as practical experience. For legally compliant use, the applicable regulations, standards, and codes as well as local conditions must always be taken into account. Technical changes, printing errors, and mistakes are reserved.

traffic areas, protection of workstations along forklift routes, picking, assembly and crossing areas, use with mixed human and vehicle traffic. A typical example is a warehouse with heavily frequented walkways along traffic routes. The FLEX+ S-Line impact protection guardrail with underrun protection reliably protects employees, creates clear structures and can be flexibly adapted or extended - seamlessly integrated into a comprehensive FLEX+ protection concept.

Properties

Application Area	Inside
Base Plate (Dimensions)	Ø850 × 6,4 mm
Certificate	PAS 13:2017
Colour	yellow / black
Design	S-Line
Diameter	204 mm
Drill hole spacing	110 × 110 mm
Fixing Holes Diameter	18 mm
Fixture	For doweling
Hazardous Goods	no
Height (Overall)	1170 mm
Main Material	Polypropylene (PP)
Material 2	Metal
Temperature Resistant	0 - 54 °
Under-run Plate (Height)	200 mm
Under-run Plate (Material Thickness)	6 mm
Underride guard (cross-section)	203,2 × 101,6 mm
Underride guard (material)	Polypropylene (PP)
Weight (gross)	18.29 kg

Accessories & Add-ons

	Category	Text	Quantity
	Consists of	BLACK BULL FLEX+ Base corner	1
	Consists of	BLACK BULL FLEX+ Base floor anchor	1
	Consists of	BLACK BULL FLEX+ concrete screw	4

Important note: The information is based on manufacturer data as well as practical experience. For legally compliant use, the applicable regulations, standards, and codes as well as local conditions must always be taken into account. Technical changes, printing errors, and mistakes are reserved.

	Category	Text	Quantity
	Consists of	BLACK BULL FLEX+ connector crossbar S- & High-Line	4
	Consists of	BLACK BULL FLEX+ post S-Line corner	1
	Consists of	BLACK BULL FLEX+ cover cap	1

Important note: The information is based on manufacturer data as well as practical experience. For legally compliant use, the applicable regulations, standards, and codes as well as local conditions must always be taken into account. Technical changes, printing errors, and mistakes are reserved.