



	Detail	Item no.
1	Railing	See table
2	Side mount L	UV1001
3	Side mount R	UV1002
4	Locking washer	UL4201
5	Bolt M10x20	BU1201/BU1200
6	Flange nut M10	MU1001/MU1010

	Detail	Item no.
7	Kick plate	SL0410/SL0510/SL0710/SL1010/SL1510/SL2010
8	Self-drilling screw 5,2x22 SS	SS5221/SS5225
9	Gull-wing coupling	MK4200
10	Tube coupling	KP4277

Edge distances apply to M12 expansion anchors in concrete




Railing	c/c
UI2042 / UB2042	1835
UI1542 / UB1542	1335
UI1042 / UB1042	835
UI0742 / UB0742	535
UI0542 / UB0542	335
UI0442 / UB0442	235




1. Installing the side mount

Screw on the left and right side mounts (2,3) with 2 fastenings (A) per mount (not included). Note! Keep track of the right and left sides.




2. Locking the railing

Assemble a nut (4) + locking washer (6) into a railing lock. Insert into the railing tube and fit a bolt (5)



3. Installing the kick plate

Any kick plate (7) is fitted with 2 self-drilling screws (8).



4. Installing couplings

Fit a gull-wing coupling (9) or tube coupling (10) between the railings.